




EPTS Torque Controlled Screwdrivers



POWER TOOL SOLUTIONS

EPTS Pneumatic Torque Controlled Screwdrivers





EPTS SCREWDRIVER FEATURES AND BENEFITS

INDUSTRIAL DUTY

- Long lasting clutch design - 2,000,000 cycle tested
- Quick shut off clutch
- Accurate torque delivery
- Simple torque adjustment
- Great power to weight for best ergonomics

EPTS-3300 Series

LIGHTWEIGHT

TORQUE RANGE
3.5 - 18.5 IN-LB

FREE SPEEDS:
1,100 / 1,700 / 2,300 RPM



EPTS-3400 Series

TORQUE RANGE
6.2 - 35.2 IN-LB

FREE SPEEDS:
800 / 1,500 / 2,100 RPM



Model	Application	Housing	Drive Size/ Chuck Capacity	Approx. Speed (rpm)	Approx. Torque Range		Weight		Length		Air Usage (cfm)	Air Inlet	Noise Level db(A)
					in-lb	Nm	lb	kg	in	mm			
Inline													
EPTS-33011-25Q	Industrial	Aluminum	1/4" QC	1,100	9.7 - 18.5	1.1 - 2.1	0.9	0.4	7.4	187	7	1/4"	70
EPTS-33017-25Q	Industrial	Aluminum	1/4" QC	1,700	6.2 - 13.2	0.7 - 1.5	0.9	0.4	7.4	187	7	1/4"	70
EPTS-33023-25Q	Industrial	Aluminum	1/4" QC	2,300	3.5 - 13.2	0.4 - 1.5	0.9	0.4	7.4	187	7	1/4"	71
EPTS-34008-25Q	Industrial	Aluminum	1/4" QC	800	14.1 - 35.2	1.6 - 4	1.4	0.7	8.2	209	10.5	1/4"	70
EPTS-34015-25Q	Industrial	Aluminum	1/4" QC	1,500	9.7 - 23	1.1 - 2.6	1.4	0.7	8.2	209	10.5	1/4"	70
EPTS-34021-25Q	Industrial	Aluminum	1/4" QC	2,100	6.2 - 19.4	0.7 - 2.2	1.4	0.7	8.2	209	10.5	1/4"	74

EPTS Pneumatic Torque Controlled Screwdrivers

EPTS-3300P Series

LIGHTWEIGHT
 TORQUE RANGE
 8.9 – 19.9 IN-LB
 FREE SPEEDS:
 1,100 / 1,700 / 2,300 RPM



EPTS-3400P Series

TORQUE RANGE
 8.9 – 33.2 IN-LB
 FREE SPEEDS:
 800 / 1,500 / 2,100 RPM



EPTS-3500P Series

TORQUE RANGE
 9.7 – 92.4 IN-LB
 FREE SPEEDS:
 500 / 800 / 1,700 RPM



Model	Application	Housing	Drive Size/ Chuck Capacity	Approx. Speed (rpm)	Approx. Torque Range		Weight		Length		Air Usage (cfm)	Air Inlet	Noise Level db(A)
					in-lb	Nm	lb	kg	in	mm			
Pistol													
EPTS-33011P-25Q	Industrial	Aluminum	1/4" QC	1,100	8.9 – 19.9	1 – 2.3	0.9	0.4	7.4	187	7	1/4"	70
EPTS-33017P-25Q	Industrial	Aluminum	1/4" QC	1,700	9.7 – 15.5	1.1 – 1.8	0.9	0.4	7.4	187	7	1/4"	70
EPTS-33023P-25Q	Industrial	Aluminum	1/4" QC	2,300	10.2 – 17.7	1.2 – 2	0.9	0.4	7.4	187	7	1/4"	71
EPTS-34008P-25Q	Industrial	Aluminum	1/4" QC	800	14.2 – 33.2	1.6 – 3.8	1.4	0.7	8.2	209	10.5	1/4"	70
EPTS-34015P-25Q	Industrial	Aluminum	1/4" QC	1,500	8.9 – 26.6	1 – 3	1.4	0.7	8.2	209	10.5	1/4"	70
EPTS-34021P-25Q	Industrial	Aluminum	1/4" QC	2,100	10.6 – 24.3	1.2 – 2.8	1.4	0.7	8.2	209	10.5	1/4"	74
EPTS-35005P-25Q	Industrial	Aluminum	1/4" QC	500	44 – 92.4	5 – 10.5	2.2	1	9.5	241	17.5	1/4"	74
EPTS-35008P-25Q	Industrial	Aluminum	1/4" QC	800	26.4 – 48.4	3 – 5.5	2.2	1	9.5	241	17.5	1/4"	75
EPTS-35017P-25Q	Industrial	Aluminum	1/4" QC	1,700	9.7 – 23	1.5 – 2.6	2.2	1	9.5	241	17.5	1/4"	75

EPTS-N3400 Series

TORQUE RANGE:
 9 – 110 IN-LB
 FREE SPEED:
 300 RPM



Model	Application	Housing	Drive Size/ Chuck Capacity	Approx. Speed (rpm)	Approx. Torque Range		Weight		Length		Air Usage (cfm)	Air Inlet	Noise Level db(A)
					in-lb	Nm	lb	kg	in	mm			
Angle													
EPTS-N34003-25	Industrial	Aluminum	1/4" sq	300	9 – 110	1 – 12	2.4	1.08	14.5	368	17.5	1/4"	75
EPTS-N34003-38	Industrial	Aluminum	3/8" sq	300	9 – 110	1 – 12	2.4	1.08	14.5	368	17.5	1/4"	75



AIMCO CORPORATE HEADQUARTERS

10000 SE Pine Street
Portland, Oregon 97216
Phone: (503) 254-6600
Toll Free: (800) 852-1368

AIMCO CORPORATION DE MEXICO SA DE CV

Ave. Cristobal Colon 14529
Chihuahua, Chihuahua. 31125
Mexico
Phone: (01-614) 380-1010
Fax: (01-614) 380-1019